3.25 83mm

FINISHED

WALL

1/2"NPT

813mm

(OR AS

REQUIRED)

16mm

COLD INLETS



PAM®II-ST COMBINATIONS

51-6D



PAM®II-ST Pressure Actuated Mixer

- Durable stainless steel balancing piston to equalize hot and cold supply pressures.
- Built-in shutoff for single handle operation
- Removable one piece upper and lower valve seat
- Internal parts of bronze and stainless steel
- Cast wall flange and lever handle, polished chrome plated
- Maximum operating pressure: 125 PSIG (860KPA)
- Adjustable high temperature limit stop set for 110°F* (43°C)
- Color coded dial, Off through Hot, with directional indicators
- 1/2" inlets and outlets
- Angle checkstops, copper tube connection
- Plasterguard/thin wall mounting bracket included.
- H-06 Institutional shower head, fixed spray, 2.5 GPM, (9.51/min)

ASSE · 1016 Certified **CSA-Certified**




Note: Leonard Valve Company reserves the right of product, or design modifications without notice or obligation.

Note: All piping and fittings not furnished by manufacturer.



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.Ca.gov



1829mm OUTLET (OR AS REQUIRED) 76mm 8.50 216mm INLET 2.38 60mm HOT AND WITH STOPS 42" 1067mm (OR AS REQUIRED) FLOOR LINE

2 25

57mm

3.25

1.625 41mm



1360 Elmwood Avenue, Cranston, RI 02910 USA Phone: 401.461.1200 Fax: 401.941.5310

> Email: info@leonardvalve.com Web Site: http://www.leonardvalve.com