


NEXT GENERATION HIGH LOW SYSTEM

TM-920B-LF-DT-RF-R34

Exposed Recirculation Piping Assemblies

TM-920B-LF-DT-RF-R34

ECO-MIX™



1 1/4" inlets and 1 1/4" outlet

- Large Type TM Thermostatic water mixing valve, adjustable high temperature limit stop*, inlet checkstops, wall support, outlet ball valve
- Small Type TM Thermostatic water mixing valve, adjustable high temperature limit stop*, inlet checkstops, outlet ball valve
- 1 1/4" inlets, 1 1/4" outlet (32mm X 32mm)
- 1 GPM (3.8 l/min) minimum flow capacity
- Inlet manifold piping
- Dura-trol® solid bimetal thermostat directly linked to valve porting to control the intake of hot and cold water and compensate for supply temperature or pressure fluctuations. Dura-trol® is highly responsive and cannot be damaged by extremes in temperature
- Adjustable high temperature limit stop* set for 120°F (49°C)
- Maximum operating pressure: 125 PSI (860 KPA)
- Combination checkstops, wall support
- Thermometer on outlet
- 3/4" Return loop with thermometer
- Ball valve
- 3/4" Leonard ARV automatic return valve, (return limiter)
- Check valves on either side of ARV
- Complete unit mounted on heavy duty strut, for ease of installation
- Valve assembly rough bronze finish
- Factory assembled and tested
- See Flow Capacity Chart see page 2
- Up to 8 GPM recirculation flow, above 8 GPM please choose RP1

OPTION

RP1- Return piping 1", ARV replaced by 1" circuit setter, method #5

Valve assembly is certified to meet Low-Lead requirements of wetted surface area containing less than 0.25% lead by weight. All other fittings and components, the sum total of which comprise the wetted surface of this product contain less than one quarter of one percent of lead by weight.

Valve assembly is ASSE 1017 certified



Valve assembly is CSA certified



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.Ca.gov

Note: Leonard Valve Company reserves the right of product, or design modifications without notice or obligation.

<p>Engineer's Approval</p>	<p>Job # _____</p> <p>Arch/Eng. _____</p> <p>Contractor _____</p>
<p>Note: The models shown represent Leonard Products which are believed to be equivalent in type and function to items specified. Leonard Valve Company is not responsible for errors or omissions due to differences in interpretations of information provided.</p>	




1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: info@leonardvalve.com

Web Site: <http://www.leonardvalve.com>

TM-920B-LF-DT-RF-R34



MINIMUM FLOW (GPM)	SYSTEM PRESSURE DROP (PSIG)										PSI
	5	10	15	20	25	30	35	40	45	50	
(l/min)	.3	.7	.97	1.4	1.7	2.1	2.4	2.8	3.1	3.4	BAR
1.0	33	47	56	63	68	82	85	92	103	115	GPM
(3.8)	98	151	212	220	238	257	280	299	318	337	l/min

NOTE: Flowrates will vary depending on existing field conditions. Leonard Valve Company always recommends using CASPAK® sizing software for proper valve sizing and model number applications.



1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: info@leonardvalve.com

Web Site: <http://www.leonardvalve.com>