

HAND SHOWERS

Submittal Data Sheet S-1139
May 2019

500P

Hand spray with non-positive push button shut-off
Braided stainless steel flexible and extended out from 60" to 84"
2 wall hooks
Double check valve backflow preventer
Supply elbow and flange
2.5 GPM (9.5 l/min.) max. flow rate

505P

- Same as above except 1.5 GPM (5.7 l/min.)



501P(G)



ADA Hand spray with non-positive push button shut-off
Braided stainless steel flexible and extended out from 60" to 84"
24" (610mm) glide rail
Double check valve backflow preventer
Supply elbow and flange
2.5 GPM (9.5 l/min.) max. flow rate

515P(G)



- Same as above except 1.5 GPM (5.7 l/min.)



501P(G)-30



- Same as above except 30" (762mm) glide, 2.5 GPM (9.5 l/min.)

515P(G)-30



- Same as above except 30" (762mm) glide, 1.5 GPM (5.7 l/min.)



501P

Hand spray with non-positive push button shut-off
Braided stainless steel flexible and extended out from 60" to 84"
24" (610mm) slide bar
Double check valve backflow preventer
Supply elbow and flange
2.5 GPM (9.5 l/min.) max. flow rate

515P

- Same as above except 1.5 GPM (5.7 l/min.)



OPTIONAL (fits all models):

SUFFIX QD - Quick connector set

For Wall Grab bars, see page 2



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.Ca.gov

500P / 505P



501P(G) / 515P(G)



501P / 515P



1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: info@leonardvalve.com

Web Site: <http://www.leonardvalve.com>

WALL GRAB BARS & HAND SHOWERS SETS

62001

24" (61 cm) ADA wall grab bar, stainless steel, 1.5" (38mm) outside diameter, concealed screw mounting system (mounting hardware included)

Slide mechanism operable by left hand, right hand, or closed first, 2.65" (67mm) lever, meets Handicapped Accessibility Standard of less than 5lb handle operating force and can swivel to ensure easy reach

Withstands 1000 lb pull (NOTE: Grab Bar must be securely attached to wall or backing to provide safety)

Wall Grab bar can be securely mounted at 90 degree angle

Hand spray with non-positive push button shut-off

Braided stainless steel flexible and extended out from 60" to 84"

2 wall hooks

Double check valve backflow preventer

Supply elbow and flange

2.5 GPM (9.5 l/min.) max. flow rate



62001-1.5

- Same as above except 1.5 GPM (5.7 l/min.)



62003

- Same as above except 36" grab bar (91 cm)

62003-1.5

- Same as above except 36" grab bar (91 cm) & 1.5 GPM (5.7 l/min.)



OPTIONAL (fits all models):

SUFFIX QD - Quick connector set



PRINTED IN USA ©2019

Leonard Valve Company

1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: info@leonardvalve.com

WEB: <http://www.leonardvalve.com>