
## INDUSTRY HOSE STATIONS





**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to <a href="https://www.P65Warnings.Ca.gov">www.P65Warnings.Ca.gov</a>

### **NOTE:**

- •Vacuum breakers NOT available
- •This unit is intended for use with water only. Follow recommended operating instructions and wear protective clothing when in use.
- •Hose and nozzle not included. If required, please attach separate submittal sheet.

Leonard Valve Company reserves the right of product, or design modifications without notice or obligation.

Engineer's Approval	Job #
	Arch/Eng.
	Contractor

© 2018 Leonard Valve Company Printed in USA

# SINGLE TEMPERATURE HOSE STATION

### ST-75-1572-LF


- 3/4" IPS water inlet
- Combination Volume control/check shutoff valve with heat resistant handle (red), #316 stainless steel body construction with stainless steel internal components
- Maximum temperature: 180°F (82°C)
- Maximum operating pressure: 125 PSI (860 KPA)
- Special bracket for direct wall mounting
- Outlet with pipe supports
- Hose connection outlet
- Stainless steel hose rack

#### **OPTIONS:**

\_\_\_\_18110 –Stainless steel mounting bracket (NOTE: not offered with BV option)

\_\_BV – Stainless ball valve in place of volume control/shutoff with pipe brackets, check valve not included

Valve Assembly is Third Party certified to meet national Low Lead requirements of AB 1953 where wetted surface area is required to be less than 0.25% lead by weight.



1360 Elmwood Avenue, Cranston, RI 02910 USA Phone: 401.461.1200 Fax: 401.941.5310

Email: <a href="mailto:info@leonardvalve.com">info@leonardvalve.com</a>
Web Site: <a href="mailto:http://www.leonardvalve.com">http://www.leonardvalve.com</a>